

Listing of Claims

1. (Original) A method of magnetic resonance imaging comprising the steps of:
 - a) providing a magnetic field within an imaging volume,
 - b) moving a subject continuously along a predetermined path,
 - c) defining a sub-volume of the imaging volume, together with the subject, the sub-volume being selected such that the time of movement of the sub-volume within the imaging volume is sufficient for magnetic resonance image data acquisition with a predefined resolution,
 - d) performing a step of magnetic resonance image data acquisition for the sub-volume,
 - e) defining a subsequent sub-volume which neighbours the sub-volume on the predetermined path to perform a subsequent step of magnetic resonance image data acquisition for the subsequent sub-volume.

2. (Original) The method of claim 1, whereby a three-dimensional imaging method is used for the step of magnetic resonance image data acquisition for the sub-volume.

3. (Currently Amended) The method of claims 1-~~or~~ 2, whereby a multislice imaging method is used for the step of magnetic resonance image data acquisition for the sub-volume, the sub-volume containing a stack of two dimensional slices along the predetermined path.

4. (Currently Amended) The method of ~~any one of the preceding claims 1, 2 or 3~~ the sub-volume having an extension along the predetermined path between 3 and 7 cm, ~~preferably 5 cm.~~

5. (Currently Amended) The method of ~~any one of the preceding claims 1 to 4,~~ the speed of movement being between 0,5 and 5 mm per second, ~~preferably between 1 and 2,5 mm per second.~~

6. (Currently Amended) The method of ~~any one of the preceding claims 1 to 5~~, whereby the magnetic resonance image data acquisition is performed by means of a parallel imaging technique.

7. (Original) The method of claim 6 whereby a SENSE-type parallel imaging technique is used.

8. (Currently Amended) The method of ~~any one of the preceding claims 1 to 7~~, the magnetic resonance image data acquisition being cyclically repeated, whereby one repetition is performed for each one of the sub-volumes.

9. (Currently Amended) The method of ~~any one of the preceding claims 1 to 8~~, the sub-volumes having a first extension along the predetermined path, the imaging volume having a second extension along the predetermined path, the second extension being at least twice the first extension.

10. (Currently Amended) A computer readable medium containing instructions for controlling a computer system ~~A computer program product, such as a digital storage medium, for magnetic resonance imaging comprising program means to perform the steps of:~~

- defining a sub-volume of an imaging volume provided by a magnetic field, continuously moving a sub-volume along a predetermined path together with a subject, the sub-volume being selected such that the time of movement of the sub-volume within the imaging volume is sufficient for magnetic resonance image data acquisition with a preferred resolution,
- defining a subsequent sub-volume which neighbours the sub-volume on the predetermined path to perform a subsequent step of magnetic resonance image data acquisition.

11. (Currently Amended) The computer readable medium ~~program product~~ of claim 10, the program means being adapted to be employed for a parallel imaging technique.

12. (Original) A magnetic resonance imaging device comprising:
- means for providing a magnetic field within an imaging volume,
 - means for moving a subject continuously along a predetermined path,
 - a control unit for generating of control signals for magnetic resonance image data acquisition within a sub-volume ($j=5, j=6$) of the imaging volume, the sub-volume being moved along the predetermined path together with the subject, the sub-volume being selected such that the time of movement of the sub-volume within the imaging volume is sufficient for magnetic resonance image data acquisition with a predefined resolution and for subsequent magnetic resonance image data acquisition within a subsequent sub-volume which neighbours the sub-volume on the predetermined path.
13. (Original) The magnetic resonance imaging device of claim 12, the means for moving being adapted to move the subject with a speed of 0.5 to 5 mm per second, preferably 1 to 4 mm per second.
14. (Currently Amended) The magnetic resonance imaging device of claims 12-~~or 13~~ further comprising means for a parallel imaging technique based on simultaneous reception through multiple receive channels.
15. (Currently Amended) The magnetic resonance imaging device of ~~any one of the preceding claims 12 to 14~~, the control unit being adapted to perform cyclic repetitions of the magnetic resonance image data acquisition.
16. (Currently Amended) The magnetic resonance imaging device of claims 12-~~to 15~~, the sub-volumes having a first extension along the predetermined path and the imaging volume having a second extension along the predetermined path, the second extension being at least twice the first extension.
17. (Currently Amended) The magnetic resonance imaging device of ~~any one of the preceding claims 12 to 16~~, the predetermined path being a straight line and the means for providing a magnetic field comprising a cylindrical magnet.

18. (Currently Amended) The magnetic resonance imaging device of ~~any one of the~~
~~preceding claims 12 to 16~~, the predetermined path being curved and the means for
providing a magnetic field comprising an open magnetic resonance system, ~~such as a C-~~
~~magnet.~~